

Model

CLASS

Article

53090-03L

Line

HORIZON

Protection

S3 SRC

Standard

EN ISO 20345:2011

Availability in stock

AVAILABLE



Sole

PU Dual-Density SRC passed

Dvokomponentni Poliuretanski đon sa samočišćećom šarom, izuzetno fleksibilan za različita mjesta upotrebe u zatvorenom i vanjskom prostoru sa SRC protivkliznim standardom

Removable insole



Antistatički apsorber u pjenastom uložku od lateksa

Protection elements

STEELPROTECTION



Čelična kapa s antikorozijskom bojom. Kapica sa kompenzacijskom gumom za udobno usjedanje. Zaštita do preko 200 J Folija od nehrđajućeg čelika sa bojom otpornom na kiselinu

Plus

Tip Plitka cipela

Gornji dio Pigmentovana koža Hydrotech
Koagulirani poliuretan

Postava 3D Air circulation 320 gr.

Uklonjivi uložak Apsorbent u pjenastom uložku od lateksa

Đon PU Dual-Density SRC passed

Zaštitna kapica ČELIČNA ZAŠTITA

Anti perforacija

Veličina 36-48

Težina gr.

590

Working environment

Multipurpose, Building, Engineering, Farming and Gardening

SRC

SRC (SRA+SRB)


Sole 52-53
PU - PU

SRA CERAMIC + DETERGENT SOLUTION	FLAT ≥ 0.32	0.42
	HEEL EN ISO 20345:2011 ≥ 0.28	0.36
SRB STEEL + GLYCEROL	FLAT ≥ 0.18	0.19
	HEEL EN ISO 20345:2011 ≥ 0.13	0.14

EN ISO 20345:2011

Antistatic

EN ISO 20345:2011 6.2.2.2.


 $0,1 < M\Omega < 1000$

ANTI-STATIC SHOE

STEELPROTECTION DUALMICRO DRIFT REFLEX INSERTS SPUNTERBO RHTHALATEFREE

SRC

Symbols



Plus



Termoformirana kruta struktura koja pruža oslonac za skočni zglob